

AMENDMENT TO THE CLAIMS

1-35 (Canceled)

36. (Currently amended) An overhead door assembly for a building having an opening to be closed by a door, the door assembly having a vertical closed position and a horizontal open position and the door assembly having dimensions that are substantially equal to the building opening, comprising:

- a frame, comprising a horizontal support member and first and second vertical members fixedly mounted to either end of the horizontal member, the vertical members fixedly mounted to a ground portion;
- a one-piece door member having a thickness including top and bottom horizontal ends and first and second vertical sides, the top horizontal end of the door member pivotally mountable to the horizontal member of the frame and the door member movable from the closed position to the open position about the pivot point;
- a hydraulic cylinder comprising a first end and a second end, the first end pivotally mountable to a portion of either one of the first and second vertical members, and the second end pivotally mountable to the door member, the hydraulic cylinder having a ram movably disposed within the hydraulic cylinder communicating an opening force and a closing force to the door member; and
- a load bearing truss externally mounted to an outside face of the bottom horizontal end of the door member providing sufficient support to the door member ~~for maintenance of~~ wherein structural integrity of the door is maintained when the door member is in the open position.

37. (Previously added) The overhead door assembly of claim 36 and further comprising a resilient weather-resistant seal disposed along the bottom horizontal end of the door member and fixedly mounted thereon, the weather-resistant seal sealing gaps between the bottom horizontal end of the door member and the ground portion.

38. (Previously added) The overhead door assembly of claim 36 and further comprising connecting means for connecting hydraulic hoses from an alternative hydraulic power source.

39. (Previously added) The overhead door assembly of claim 36, wherein a cycle time for opening or closing the door member is between 28 to 32 seconds.

40. (Previously added) The overhead door assembly of claim 36, wherein a cycle time for opening or closing the door member is not greater than about 32 seconds.

41. (Previously added) The overhead door assembly of claim 36, wherein the door member closes flush with a building surface.

42. (Previously added) The overhead door assembly of claim 36 and further comprising a resilient seal for sealing a perimeter of the door member and providing a weather tight seal around all four sides of the door member.

43. (Previously added) The overhead door assembly of claim 36 and further comprising a three position hydraulic valve for controlling the direction of the door member.

44. (Previously added) The overhead door assembly of claim 43 and further comprising check valve locks for locking the door member in a selected position.

45. (Previously added) The overhead door assembly of claim 36, wherein the hydraulic cylinder further comprises a mechanical stop disposed within the cylinder.

46. (Previously added) The overhead door assembly of claim 36, wherein the frame is anchored to a concrete footing.

47. (Previously added) The overhead door assembly of claim 46, wherein the frame is anchored to the concrete footing with anchor bolts fastened to the concrete footing.

48. (Previously added) The overhead door assembly of claim 36, wherein the frame structure supports a substantial portion of the load of the door member.

49. (Currently amended) An overhead door for a building having an opening to be closed by the door, the door having a vertical closed position and a horizontal open position and the door having dimensions that are substantially equal to the building opening, comprising:
a one-piece door member having a thickness including top and bottom horizontal ends and first and second vertical sides;
means for fixedly mounting the top horizontal end of the door member to a support structure;
means for mounting to the door member a mechanism adapted and configured to open and close the door member; and
an external load bearing truss fixedly attached to an outside face of the door member providing sufficient support to the door member ~~for maintenance~~ of wherein structural integrity of the door is maintained when the door member is in the open position.

50. (Previously added) The overhead door of claim 49 and further comprising a sealing means for sealing the bottom horizontal end of the door member against a ground portion.

51. (Previously added) The overhead door of claim 51, wherein the sealing means comprises resilient weather-resistant seal disposed along the bottom horizontal end of the door member and fixedly mounted thereon, sealing gaps between the bottom horizontal end of the door member and the ground portion.

52. (Previously added) The overhead door of claim 49, wherein the mounting means, fixedly mounting the top horizontal end of the door member to the support structure comprises a plurality of pairs of hinges fastened with a plurality of bolts.

53. (Previously added) The overhead door of claim 49 and further comprising closing means, closing the door flush with the building opening.

54. (Previously added) The overhead door of claim 53, wherein the closing means, closing the door flush with the building opening comprises angled members that overlap the building opening.

55. (Previously added) The overhead door of claim 53, wherein the closing means further comprises a seal.

56. (Previously added) The overhead door of claim 55, wherein the seal comprises a compressed foam seal.

57. (Currently Amended) An overhead door having a vertical closed position and a horizontal open position provided in a building having an opening to be closed by the door, the overhead door having dimensions that are substantially equal to the building opening, comprising:

 a one-piece door member having a thickness including top and bottom horizontal ends and first and second vertical sides;

 means for fixedly mounting the top horizontal end of the door member to a support structure;

 means for mounting to the door member a mechanism adapted and configured to open and close the door member; and

an external load bearing truss fixedly mounted to an outside face of the door member providing sufficient support to the door member ~~for maintenance of~~ wherein structural integrity of the door is maintained when the door member is in the open position.

58. (Previously added) The overhead door of claim 57 and further comprising sealing means, sealing the bottom horizontal end of the door member against a ground portion.

59. (Previously added) The overhead door of claim 58, wherein the sealing means comprises a resilient weather-resistant seal disposed along the bottom horizontal end of the door member and fixedly mounted thereon, sealing gaps between the bottom horizontal end of the door member and the ground portion.

60. (Previously added) The overhead door of claim 57, wherein the mounting means, fixedly mounting the top horizontal end of the door member to the support structure comprises a plurality of pairs of hinges fastened together with a plurality of bolts.

61. (Previously added) The overhead door of claim 57, wherein the mounting means, mounting the door member to the mechanism adapted and configured to open and close the door member comprises a hydraulic cylinder.